

COFFEE-PRO MOISTURE-MAC



EASY TO USE

RUGGED PORTABLE DESIGN

NO SAMPLE PREPARATION REQUIRED

AVERAGING FACILITY

LANGUAGE OPTIONS IN ENGLISH, SPANISH, PORTUGESE, GERMAN, AND FRENCH

MULTI POINT CALIBRATION AVAILABLE

HIGHER FREQUENCY CAPACITIVE CIRCUIT FOR ENHANCED ACCURACY

ROBUST TEMPERATURE COMPENSATION CIRCUIT

Coffee Pro Moisture Mac

Coffee Pro Moisture Mac Kit with density scale

SPECIFICATIONS:

Operating Range (Moisture): 5% to 40% depending on

grain tested in ten seconds.

Operating Range (Temperature): 32° - 113° F (0° - 45° C).

Repeatability: +/- 0.5% in normal

moisture range

Accuracy: +/- 0.5% in normal

moisture range

Display Resolution:

0.1% moisture.

2 year warranty in North America and 1 year overseas.

No charts to read or complicated instructions, meaning virtually no operator training is required. No moving parts reduces down time for calibrations, adjustments, or repairs

Compact design is great for testing for coffee or grain moisture at remote locations. Calibrations include Arabica, Robusta, Dry Cherry, Parchment, and Cocoa. Raw data values (Bit Values) may be used with a spreadsheet to establish moisture curves for any suitable commodity





Deluxe Model Available with field density scale, and hard carry case

Packed Dimensions & Weight

Moisture Mac L 228 mm x W 127 mm x H 178 mm Weight 1.4 kg Moisture Mac Kit L 407 mm x W 407 mm x H 204 mm Weight 3.2 kg

QUICK QUOTE

ONLINE PRICING